
# **AMERICAN INTERNATIONAL INDUSTRIES**



# MATERIAL SAFETY DATA SHEET

# Section 1. Product and Company Identification

DATE: 6/18/2009 Product Name: Seche Natural

Formula: 30-2166 REV. 00

Item#: 83143

Manufacturer: American International Industries

2220 Gaspar Ave

Los Angeles, CA 90040

Chem-Tel: (800) 255-3924

# Section 2. Composition / Information on Ingredients

#### **Hazardous Ingredients:**

	Component	CAS#	90	Exposure Limits ppm
_				ACGIH-TWA / OSHA-PEL
	Ethyl Acetate	141-78-6	30 - 50%	ACGIH-TWA: 400ppm
				OSHA-PEL: 400ppm
	Nitrocellulose	9004-70-0	5 - 20%	ACGIH-TWA: 400ppm
	Butyl Acetate	123-86-4	30 - 50%	ACGIH-TWA: 100ppm
				OSHA-PEL: 150ppm
	Isopropyl Alcohol	67-63-0	1 - 5%	ACGIH-TWA: 400ppm
	SD Alcohol 40-B	N/A	5 - 15%	ACGIH-TWA: 1000ppm
				OSHA-PEL: 1000ppm

### Section 3. Hazardous Identification

### Potential Health Effects, Signs and Symptoms of Exposure:

May cause irritation or burning eyes. Eye:

Skin: Repeated or prolonged liquid contact may cause skin irritation with discomfort or dermatitis.

Gastro intestinal distress, call a physician. Ingestion:

May cause nose and throat irritation. Inhalation:

#### Section 4. First Aid Measures


First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if

discomfort persists.

First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact

a physician.





# **MATERIAL SAFETY DATA SHEET**

First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give

anything by mouth to an unconscious person. Seek prompt medical attention.

### **Section 5. Fire Fighting Measures**

Flash Point (°F/°C): 24°F (-4°C)TCC

Flammable Limit LEL: Not determined (vol%): UEL: Not determined

Auto-ignition Temp.

(vol%)

None Established

Extinguisher Media: Foam, dry chemical or carbon dioxide.

Fire Fighting Full protective equipment, including self contained breathing apparatus is recommended.

Procedures: Water from fog nozzle may be used to cool containers to prevent pressure build up.

Unusual Fire and

When heated above the flash point flammable vapors may be emitted. Fine mists or sprays

Explosion Hazards: may be flammable at temperatures below the flash point.

### Section 6. Accidental Release Measures

Spill or Release Procedures:

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802 in case if the spill is in excess of EPA reportable quantity.

# Section 7. Handling and Storage

Handling & Storing: In accordance with good industrial practice avoid unnecessary personal contact. Wash face and

hands before eating, drinking, or smoking. Store in original container, away from excessive


heat and keep in a dry are.

### Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Ventilation: Use local Exhaust.

## **AMERICAN INTERNATIONAL INDUSTRIES**



# **MATERIAL SAFETY DATA SHEET**

Protective Gloves: Neoprene gloves.

Eye Protection: Include splash guards and side shields.

Respiratory Protection: Use with adequate Ventilation and avoid breathing vapors.

Clothing: Coveralls.

Other Protective Eye bath and shower.

### Section 9. Physical and Chemical Properties

Appearance @ 25°C: Clear viscous liquid Viscosity (RAT): Not applicable

Odor @ 25°C:Strong SolventVapor Pressure:Not AvailablepHNot applicableVapor Density:Not AvailableSpecific Gravity:Not determinedEvaporation Rate:Slower than etherIgnition:Not applicableWT/GAL:8.19

Ignition:Not applicableMelting Point:Not applicableBoiling Range:171 - 640°FSolubility in WaterModerate

# Section 10. Stability and Reactivity

Stability: Stable

**Hazardous Decomposition Products:** 

CO, CO2, Nitrous Oxides, Smoke

Incompatibility (Materials to Avoid):

Acids, Alkalies and Peroxides.

**Hazardous Polymerization:** 

Will not occur


Conditions to Avoid: Do not store over 120°F

# Section 11. Toxicological Information

Results of component toxicity test performed:

No data

#### **AMERICAN INTERNATIONAL INDUSTRIES**



# MATERIAL SAFETY DATA SHEET

Human experience:

No data

# Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:

No data

### Section 13. Disposable Considerations

RCRA 40 CFR 261 Classification:

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal. Do not incinerate in closed containers

# Section 14. Transportation Information

<DOT Information>

Proper Shipping Name: Paint

DOT Hazard Class: 3, Flammable Liquid

Packaging Group:

UN ID Number UN 1263

# Section 15. Regulatory Information

United States Federal Regulations

MSDS complies with OSHA's Hazard Communication Rule 29, CFR 1910.1200

SARA: See section 2 for reportable material

SARA Title III: See Section 2

RCRA: No Data

TSCA: Components listed. CERCLA: See Section 2

State Regulations

California Proposition 65: Toluene

International Regulations Canada WHMIS: No Data

Europe EINECS Numbers: No Data





# **MATERIAL SAFETY DATA SHEET**

# Section 16. Other Information

No additional information available.