



MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name: Seche Vite Dry Fast Top Coat
Formula: 30-3015
Item#: 83086, 83105, 83005, 83109, 83050, 83132, 83099, 83040, 29903
DATE:
REV.
Manufacturer: American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Component	CAS #	%	Exposure L ACGIH-TWA /
Butyl Acetate	123-86-4	42.2	TLV/PEL:
*Toluene	108-88-3	21.5	TLV/PEL:
Cellulose Acetate Butyrate	9004-36-8	17.5	None Esti
Isopropyl Alcohol	67-63-0	14.25	TLV/PEL:
Trimethyl Pentanyl Diisobutyrate	6846-50-0	4.5	None Esti
Benzophenone-1	131-56-6	0.1	None Esti

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of the Title III and of 40 CFR 372.

Components in this product have been verified as being on the TSCA Inventory and has been classified in accordance with the hazard criteria of the CPR as required.

WARNING: "THIS PRODUCT CONTAINS TOLUENE, A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS AND REPRODUCTIVE HARM"

Section 3. Hazardous Identification

Inhalation Health Risks and Symptoms of Exposure

Breathing high concentrations of vapors or mist may cause irritation of the nose and throat. Signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue.)

Skin and Eye Contact Health Risks and Symptoms of Exposure

Eye: This product may cause eye irritation. Direct contact with this material or exposure to its vapors or mists (greater than approximately 1000 ppm) may cause burning, tearing, redness, and swelling.



MATERIAL SAFETY DATA SHEET

Skin: This product may cause skin irritation. Prolonged or repeated exposure to this material may cause redness, drying and cracking of and dermatitis.

Ingestion Health Risks and Symptoms of Exposure

Ingestion of excessive quantities may cause irritation of the digestive tract. Signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue.)

Health Hazards (Acute and Chronic)

No ingredient present in this product is identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA. However, repeated and prolonged occupational over exposure to solvent present on this product with potential for brain and nervous system damage (sometimes referred to as a solvent or painter's syndrome). Intentional misuse, such as deliberately concentrating and inhaling this product may be harmful or fatal.

Section 4. First Aid Measures

Emergency and First Aid Procedures

Inhalation: In case of irritation by vapor, remove from exposure, treat symptomatically, and get medical attention if symptoms persist.

Eyes: Any material that contacts the eye should be washed out immediately and medical attention obtained if symptoms persist.

Skin: Wash with soap and plenty of water.

Ingestion: Call a physician or poison control center immediately. Induce vomiting as directed by medical personnel.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 24°F (-4.44°C) (TCC)

Flammable Limit (vol%): Lower: 1.2
Upper: 12.7

Auto-ignition Temp. (vol%): None Established

Extinguisher Media: Water is the most effective fire extinguishing medium for Nitrocellulose. It is recommended to use in a large volume. Dry chemical, CO₂ or a universal type foam could be used to extinguish fires.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with eyes. Use water spray to keep fire-exposed containers cool.

Unusual Fire and Explosion Hazards: Material is flammable. Vapors may travel considerable distance to a source of ignition and back. Keep away from heat, sparks, and flame. Keep container closed. Use with adequate ventilation.

Section 6. Accidental Release Measures



MATERIAL SAFETY DATA SHEET

Spill or Release Procedures: Highway or railway spills call chemtrec (800) 424-9300 cont. U.S. Collect (202) 483-7611 and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and absorb spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

Section 7. Handling and Storage

Handling & Storing: In accordance with good industrial practice avoid unnecessary personal contact. Wash hands before eating, drinking, or smoking. Store in original container, away from excess moisture and keep in a dry area.

Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Ventilation: The ventilation system should be designed to be able to maintain airborne concentration at or below the established exposure limits. If the current ventilation is not adequate to maintain this level, additional ventilation or exhaust systems may be required. Use explosion proof equipment.

Protective Gloves: The use of gloves impermeable to the specific material is advised to prevent skin contact and possible irritation.

Eye Protection: Safety glasses with side shields (or goggles) are recommended for any type of industrial handling.

Respiratory Protection: When vapor concentration exceeds the established exposure limits respiratory protection is necessary. Depending on the airborne concentration, use a respirator or a gas mask with appropriate cartridges and canisters (NIOSH approved organic vapor) or supplied air equipment.

Other Protective Clothing or Equipment: The use of gloves impermeable to the specific material is advised to prevent skin contact and possible irritation. Use splash goggles (NIOSH approved) to safeguard against potential eye irritation or injury.



MATERIAL SAFETY DATA SHEET

Preventative Measures: Keep containers and storage containers closed when not in use. Do not store near heat, flame, or strong oxidents. While transferring this material the containers used in this process must be effectively grounded (ultimately to an earth ground) to prevent fire or explosion risk from static accumulation in accordance with the National Fire Protection Association standard for flammable liquid products.

Section 9. Physical and Chemical Properties

Appearance @ 25°C:	Transparent viscous liquid	Viscosity (RVT):	Not applicable
Odor @ 25°C:	Sweet Ester Odor	Vapor Pressure:	Not Available
pH	Not applicable	Vapor Density:	Not Available
Specific Gravity:	7.634 lb/gal	Material V.O.C.:	.53 lb/gal
Ignition:	Not applicable		
Melting Point:	Not applicable		
Boiling Range:	117°F - 228°F		
Solubility in Water	Partial		

Section 10. Stability and Reactivity

Stability: Stable

Hazardous Decomposition or Byproducts:

Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, and nitrogen oxide. Under some conditions, methane, irritating aldehydes and carboxylic acids, and hydrogen cyanide may be formed.

Incompatibility (Materials to Avoid):

This product is incompatible with strong acids or bases and oxidizers.

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Flames, electric spark, static, and heat.

Section 11. Toxicological Information

Results of component toxicity test performed:

No data

Human experience:

No data



MATERIAL SAFETY DATA SHEET

Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:

No data

Section 13. Disposable Considerations

Dispose of product in accordance with local, county, state, and federal regulations.

Section 14. Transportation Information

<DOT Information>

Proper Shipping Name:	Paint
DOT Hazard Class:	3, Flammable Liquid
Packaging Group:	II
UN ID Number	1263

Section 15. Regulatory Information

Data Available Upon Request.

Section 16. Other Information

No additional information available.

1/18/11
03

imits ppm
' OSHA-PEL
150ppm

200ppm

ablished
400ppm
ablished
ablished

nd all information

) OTHER

stem

ater than

_____ and burning,

e.g.,

IA. Reports
menant
e by

if symptoms

ymptoms

I. Never give

ed to be
xtiguish small

n skin and

nd flash
late

6 from Alaska

way from spill.
contain spill.
otify
one number:

face and
sive heat

ions below
s level,
ent.

ct and

il chemical

r is
with
quipment.

ct and
l eye contact,

at, sparks,
cess has to
rom static
petroleum

de, and
ids and

Date	Revision	Comments
18-Mar-10	01	Modified flash point from -4.4 to -4.44C.
24-Aug-10	02	Adjusted percent from 30-40 to 20-25.
22-Sep-10	03	Entered all ingredients and percent in composition