SAFETY DATA SHEET

JoiMist Medium Styling & Finishing Spray (55% VOC)



Section 1. Identification

Product Name	: JoiMist Medium Styling & Finishing Spray (55% VOC)
Other means of identification	: Not available.
Recommended use	: Hair Care Product
Restrictions on use	: Use only as directed on the product label.
Manufacturer	: Zotos International, INC 100 Tokeneke Road, Darien, CT 06820 www.zotos.com
Validation date	: 5/18/2020
In case of emergency	: (800) 584-8038 [24 Hours]
<u>Telephone number</u>	: (203) 656-7859 [8:30 a.m 5:00 p.m.]
Transportation Emergency	: Contact: CHEMTREC 1-800-424-9300 [US/Canada 24 Hours]
Product type	: Aerosol.

Section 2. Hazards identification

Emergency overview

NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Additional information on toxicological endpoints is available from the supplier upon request

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas
	Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 46% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 98.7% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 46%
GHS label elements	

Hazard pictograms

Signal word	: Danger				
Hazard statements		flammable aerosol. as under pressure; may e	explode if heated.		
Precautionary statements					
General		before use. Keep out of uct container or label at ha		medical advice is need	ed,
Prevention	smoking. I	r from heat, hot surfaces, Do not spray on an open Do not pierce or burn, eve	flame or other ignitior		ces. No
Response	: Not applica	able.			
Storage		m sunlight. Do not expos ilated place.	e to temperatures ex	ceeding 50 °C/122 °F.	Store in
		7656			
Date of issue/Date of revision	: 5/18/2020	Date of previous issue	: 3/31/2015	Version : 1	1/11

Section 2. Hazards identification

Disposal

: Not applicable.

Hazards not otherwise

: None known.

classified

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

United States

Name	%	CAS number
ethanol	52.69	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary fi	rst aid measures
Eye contact	 In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
Inhalation	: Move affected person to fresh air.
Skin contact	: Remove contaminated clothing and shoes. Wash with plenty of soap and water.
Ingestion	: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Treat symptomatically. Never give anything by mouth to an unconscious person. Call a physician.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: None.
Specific treatments	: No specific treatment.
Protection of first-aiders	 No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

7656

Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds carbonyl halides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	•	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble.
Large spill	:	Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	container: p not pierce o clothing. Av ventilation. away from h	opriate personal protecti protect from sunlight and r burn, even after use. I void breathing gas. Avoi Wear appropriate respir neat, sparks, open flame entilating, lighting and ma	do not expose to tem Do not ingest. Avoid of d breathing vapor or r ator when ventilation or any other ignition	peratures exce contact with eye nist. Use only is inadequate. source. Use ex	eding 50°C. Do es, skin and with adequate Store and use cplosion-proof
		7656			
Date of issue/Date of revision	: 5/18/2020	Date of previous issue	: 3/31/2015	Version	:1 3/11

Section 7. Handling and storage

Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources.

Section 8. Exposure controls/personal protection

United States

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
ethanol	ACGIH TLV (United States, 3/2015). STEL: 1000 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures	
Hygiene measures :	
Hygiene measures :	When using do not eat, drink or smoke.
Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	7656

 Date of issue/Date of revision
 : 5/18/2020
 Date of previous issue
 : 3/31/2015
 Version
 : 1

Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid. [Viscous liquid.]
Color	: Colorless to light yellow.
Odor	: Characteristic. Fragrance-like.
рН	: 6 to 9
Boiling point	: 78.333°C (173°F)
Flash point	: Closed cup: 13°C (55.4°F)
Relative density	: 0.81 to 0.85
Aerosol product	
Type of aerosol	: Spray
Heat of combustion	: 7.637 kJ/g

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.Chemical stability: The product is stable.Possibility of hazardous
reactions: Under normal conditions of storage and use, hazardous reactions will not occur.Conditions to avoid: Avoid all possible sources of ignition (spark or flame).Incompatible materials: No specific data.Hazardous decomposition
products: Under normal conditions of storage and use, hazardous decomposition products should

Section 11. Toxicological information

United States

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor LD50 Oral		124700 mg/m³ 7 g/kg	4 hours -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.0666666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related	to the physical, chemical and toxicological characteristics

Section 11. Toxicological information

Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of toxic	i <u>ty</u>
Acuto toxicity astimates	

Acute toxicity estimates

Not available.

Section 12. Ecological information

United States

Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
		franciscana - Larvae	
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low

Section 12. Ecological information

Mobility in soil

Soil/water partition : Not available.

coefficient (Koc) Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols	2.1	-		Limited quantity Yes. Packaging instruction Exceptions: 306. Non-bulk: None. Bulk: None. Quantity limitation Passenger aircraft/rail: 75 kg. Cargo aircraft: 150 kg. Special provisions 153, N82
TDG Classification	UN1950	AEROSOLS. Marine pollutant (ethanol)	2.1	-		Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail. <u>Explosive Limit and Limited Quantity Index</u> 1 <u>Passenger Carrying Road or Rail Index</u> 75
Mexico Classification	UN1950	AEROSOLES	2.1	_		Special provisions 63, 190, 277
ADR/RID Class	UN1950	AEROSOLS	2	-		Limited quantity LQ2 Special provisions 190 327 625 Tunnel code (D)
1	1	7656	l	I	1	1

Section 14. T	ransport	information				
IMDG Class	UN1950	AEROSOLS. Marine pollutant (ethanol)	2.1	-		The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency schedules</u> F-D, S-U <u>Special provisions</u> 63, 190, 277, 327, 959
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-	Y	The environmentally hazardous substance mark may appear if required by other transportation regulations. Quantity limitation Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203. Special provisions A145

PG* : Packing group

Section 15. Regulatory information

0		
U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined	
	United States inventory (TSCA 8b): Not determined.	
	Clean Air Act (CAA) 112 regulated flammable substances: 1,1-difluoroethane	
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed	
Clean Air Act Section 602 Class I Substances	: Not listed	
Clean Air Act Section 602 Class II Substances	: Not listed	
DEA List I Chemicals (Precursor Chemicals)	: Not listed	
DEA List II Chemicals (Essential Chemicals)	: Not listed	
SARA 302/304		
Composition/information of	on ingredients	
No products were found.		
SARA 304 RQ	: Not applicable.	
<u>SARA 311/312</u>		
Classification	: Fire hazard Sudden release of pressure	
Composition/information on ingredients		
	7656	

Date of issue/Date of revision : 5/18/2020 Date of previous issue : 3/31/2015 Version :1

Section 15. Regulatory information

Name	%	hazard	Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
ethanol	52.69	Yes.	No.	No.	Yes.	No.

State regulations

84.0			
wa	ssa	cnu	setts

- : The following components are listed: ETHYL ALCOHOL; DIFLUOROETHANE
- : None of the components are listed.

New York New Jersey

- : The following components are listed: ETHYL ALCOHOL; ALCOHOL; 1,
- 1-DIFLUOROETHANE; ETHANE, 1,1-DIFLUORO-
 - : The following components are listed: DENATURED ALCOHOL; ETHANOL

Pennsylvania California Prop. 65

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. This product is not known to the State of California to cause cancer. Not available.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

<u>Canada</u>

WHMIS (Canada)	 Class B-2: Flammable liquid Class B-5: Flammable aerosol. Class D-2B: Material causing other toxic effects (Toxic).
<u>Canadian lists</u>	
Canadian NPRI	: The following components are listed: Ethanol; Volatile organic compounds
CEPA Toxic substances	: The following components are listed: Volatile organic compounds
Canada inventory	: Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.



Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>History</u>	
Date of printing	: 5/18/2020
Date of issue/Date of revision	: 5/18/2020
Date of previous issue	: 3/31/2015
Version	: 1
References	: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

7656